

COLOR REFLECTION DENSITOMETER

R
7
2
0



- Density
- Density Difference
- Dot Area
- Dot Gain
- Auto Function

R720 COLOR REFLECTION DENSITOMETER

HIGH PERFORMANCE & RELIABILITY

Ihara Electronic Industries utilizes advanced microcomputer technology to ensure superior performance and reliability for its entire line of densitometric products. Standard functions include: *density, density difference, dot area, dot gain and auto-function.*

MENU DRIVEN COMMANDS

Simply select the functions desired. No memorization or operation manual required.

SELF-GUIDING PROMPTS

Clear and concise instructions are prompted across the large graphic LCD display in every measurement.

HELP KEY PROVIDES EXPLANATION OF KEY FUNCTIONS

Detailed explanations are available for all measurement functions along with answers to frequently asked questions.

UPGRADEABLE DESIGN

To increase measurement functions upgrade to the model R730 for a nominal fee. Contact your dealer or IHARA for more information.

QUICK CALIBRATION

It takes seconds to calibrate using the quick calibration function. Standard calibration is also available.

AUTO-FUNCTION

Auto-function allows the user to measure density and dot gain, interchangeably.

LARGE GRAPHIC LCD DISPLAY

The easy to read graphic LCD display allows the user to determine the precise configuration desired, including right or left handed view, two or three decimal precision and display options.

PRINTER AND COMPUTER INTERFACE

The configurable RS-232C serial interface is capable of linking the R720 to a computer or to the IHARA PR-95 printer.

SECURITY USER CODE (OPTIONAL)

As an option to safeguard your investment, the R720 may be set to operate only with the correct user code.



IHARA R720 B & W REFLECTION DENSITOMETER SPECIFICATIONS

- **MEASUREMENT FUNCTIONS**
 - Density
 - Density Difference
 - Dot Area (Murray-Davies or Yule-Nielsen)
 - Dot Gain
 - Auto-Function (Automatically measures density or dot gain)
- **FILTER RESPONSE**
 - Status T
 - Status E
 - Status A
- **MEASURING GEOMETRY**
 - 0°/45° (ANSI PH2.17, ISO 5/4, DIN 16536)
- **MEASURING RANGE**
 - Density 0.00D - 2.50D
 - Dot Area 0% - 100%
- **REPEATABILITY**
 - ± 0.01D or 1%
- **ACCURACY**
 - ± 0.02D or 2%
- **LIGHT SOURCE**
 - Halogen Lamp, Approximately 2856°K
- **APERTURE DIAMETER**
 - 3.0mm (1.7mm optional)
- **DETECTOR**
 - GaAsP Photodiode
- **DISPLAY**
 - 128 x 64 Dot Graphic LCD
- **POWER SUPPLY**
 - Ni-Cad (4.8V), 800mAh
- **RECHARGE TIME**
 - Approximately 1.5 hours
- **MEASUREMENTS PER CHARGE**
 - Approximately 4,000 (Internal Testing)
- **WARM UP TIME**
 - None
- **MEASURING TIME**
 - Approximately 1 second
- **OPERATING TEMPERATURE RANGE**
 - 41°F ~ 104°F (5°C ~ 40°C)
- **POLARIZATION FILTER**
 - (Optional)
- **SECURITY USER CODE**
 - (Optional)
- **DIMENSIONS**
 - 2 3/4"W x 2"H x 8 1/4"L
 - (72mm x 50mm x 210mm)
- **WEIGHT**
 - 1.2 lbs. (With Batteries)
 - (530 g)
- **COMPUTER OUTPUT**
 - Configurable RS-232C Serial Interface
- **ACCESSORIES**
 - Operation Manual
 - Calibration Standard
 - AC Adapter (9V, 500mA, center-negative)
 - Carrying Case
 - Serial Interface Cable (Optional)
 - Ihara PR-95 Printer (Optional)
 - Software (Optional)
 - Cable Harness (Optional)

Specifications subject to change without notice.
Printed in USA • Form R720-AW (10/06)

IHARA

JKang
环境解决方案专家

深圳市净康科技有限公司

王经理 15813841944 (微信同号) QQ: 422612157 电话: 0755-28917660

邮箱: jkang66@163.com 网址: <http://www.3000buy.com>

地址: 深圳市龙岗区南湾街道吉厦社区沙平北路 111 号 6008